Immersion thermostat for baths "Digit-Cool"

DIGITAL SELECTOR AND TEMPERATURE CONTROL ADJUSTABLE FROM 0 °C TO 100 °C.
STABILITY: 100 °C ±0.1 °C, AND AT 0 °C ±0,1 °C. SET ERROR: ±0.1 °C. RESOLUTION: 0.1 °C.

SAFETY: STANDARD DIN 12876. SAFETY OVER TEMPERATURE THERMOSTAT WITH ADJUSTABLE MANUAL RESET. LOW LIQUID LEVEL SENSOR PROTECTION.

Autonomous unit with cooling system

Compressor unit built-in

FEATURES

Maximum volume to achieve the working temperature: 20 litres.
Minimum depth of the elements with contact with the liquid: 15 cm.
Hermetically sealed compressor.
RS-232 out put to a computer control or printer.
Portable control and stirring unit with lifting handle.

CONTROL PANEL

Main power switch.
LCD Display showing working parameters.
Push button configuration selector.
Push button parameter selection.
Push button increase/decrease set value.
Start / Stop, push button.





Digitcool thermostat with bath and 4 place ring set lid.

MODEL

Part No.	Control Range °C	Height / Width / Depth (exterior) cm	Pump Pressure / Flow H_2O	Power W	Power H.P.	Weight Kg
3001373	0 +100	45 21 51	150 mbar / 12 l/min	1460	1 / 5	22

ACCESSORIES for thermostatic unit digit-cool.

Stainless steel baths.
Double skinned with an AISI 304 stainless steel exterior with a bath of AISI 304 stainless steel interior.
Supplied with a drain tap and lifting handles.





1. Lifting rack support. .
Capacity 3 tube racks. Part No. 1001296
2. Tube racks for lifting rack support.

Part No.	For Ø tubes mm	Capacity Rack tubes	Height / Width / Depth (exterior) cm
1001202	13	36	8 8.2 23.6
1001203	16	24	8 8.2 23.6
1001204	20	24	8 8.2 23.6

MODELS

Part No.	Capacity litres	Height / Width / Depth (usable) cm	Height / Width / Depth (exterior) cm	Weight Kg
6000392	20	15 48 30	20 55 35	6.6
6000393	27	20 48 30	25 55 35	7.6



Ring set lid 105, 80, 60 and 37 mm Ø reduction rings and a check thermometer location hole in the lid.
Capacity 4 places.
Part No. 1001374

Digitcool thermostat with bath and 4 place ring set lid.