High speed centrifuges with microprocessor control “Centronic BLT” and “Centrofriger BLT”

Versatile. Large range of rotors and adapters. Maintenance free induction motor drive.



Model “Centronic BLT”

Control panel features (see page 121).
External case of DUR-AL alloy with ABS plastic coated front AISI 304 stainless steel bowl.



Model “Centrofriger BLT” refrigerated, temperature range -12 °C to 40 °C.

MODEL

Part No.	Max. Volume ml	Max. number of tubes	Height / Width / Depht (exterior) cm	Power W	Weight Kg
7001768	400	4 x 100 ml	34 41 54	440	22

MODEL

Part No.	Max. Volume ml	Max. number of tubes	Height / Width / Depht (exterior) cm	Power W	Weight Kg
7001769	400	4 x 100 ml	34 41 71	960	39

Note: The rotor being used limits the actual temperature in the chamber due to the speed and ambient temperature. Internal temperature indicated on the LCD display.

ACCESSORIES

Angle rotors with lid, made of anodised hardened aluminium with identification system. All rotors are autoclavable.



7001670



7001324



7001706



7001325



7001323



7001671



7001672



7001673



7001408



With calculator reader

Part No. head	Rotor type	Max. volume	Tubes capacity	Ø x Length mm	CENTRONIC BLT Max. R.p.m	CENTRONIC BLT Max. R.c.f. (xg)	CENTROFRIGER BLT Max. R.p.m	CENTROFRIGER BLT Max. R.c.f. (xg)
7001670	Angle+lid	270 ml	18 x 15 ml	16.5 x 100	11000	14492	11000	14492
7001706	Angle+lid	400 ml	8 x 50 ml	34 x 100	12000	16913	12000	16913
7001325	Angle+lid	300 ml	6 x 50 ml	29 x 103	12000	16913	12000	16913
7001324	Angle+lid	180 ml	6 x 30 ml	25 x 92	13500	16900	15300	21713
7001323	Angle+lid	100 ml	10 x 10 ml	16 x 80	13500	18335	15300	23550
7001671	Angle+lid	40.5 ml	18x0.25/0.5 ml + 18x1.5/2.2 ml	-	13500	15992	15300	20541
7001672	Angle+lid	60 ml	40 x 0.25/0.5 ml	-	13500	16250	15000	20100
7001673	Angle+lid	45 ml	30 x 1.5/2.2 ml	-	13500	19048	15000	23716
7001408	Angle+lid	Microhaematocrit	24	1.4 x 75	12000	15935	12000	15935

Note: All buckets and adapters come without tubes unless stated, see page 137 for tubes and accessories.