Glass drying oven “Dryglass”

FAN ASSISTED AIR CIRCULATION.
ADJUSTABLE TEMPERATURE FROM 40 °C TO 170 °C.

SAFETY:
EN.61012 STANDARD OVER TEMPERATURE SAFETY CUT OUT FITTED.
DIN 12880. STANDARD (CLASS 2 AND 3.1) ADJUSTABLE SAFETY THERMOSTAT FITTED.



FEATURES

Hydraulic thermostat for temperature control.
Air circulation by turbo fan.
Inner chamber made of AISI 304 stainless steel with shelf runners.
Removable tempered glass sliding doors.
Ventilation port for steam.
Epoxy coated external case.

STANDARD EQUIPMENT

2 shelves and 4 shelf guides.

CONTROL PANEL

Dual heating power selector switch.
Mains indicator lamp.
Hydraulic thermostat for temperature control.
Locking system of thermostat knop.
Heater “ON” operation indicator lamp.
Analogue thermometer.
Adjustable over temperature safety thermostat, that cuts off the power if the control thermostat fails, manual reset with “on” indicator lamp.

MODEL

Part No.	Capacity litres	Height / Width / Depth (interior) cm			Height / Width / Depth (exterior) cm			Shelf Positions	Power W	Weight Kg
2000381	126	45	70	40	66	94	54	8	3000	65

ACCESSORIES

Accessories must be factory installed.



Part No.

2000002 **Timer switch** 0-120 minutes.

2000009 **24 hour programmer** with continuous on/off cycling up to every 15 minutes.

SPARES

Part No.
2000081 **Shelf guides** x 2.
2000091 **Shelf.**
Each shelf requires 2 guides.