Vacuum pump “2XZ - 2B”

ROTARY VANE PUMPS WITH BUILT-IN OIL CHECK VALVE FOR GENERAL VACUUM APPLICATIONS.
MOTOR WITH THERMAL PROTECTOR AND START SWITCH.

FEATURE

Asbestos-free vanes and gaskets.
Suction port of Ø 25 mm.
Analog vacuum gauge.
Large oil volume and forced lubrication.
Oil tank capacity: 1150 ml
Expulsion filter for oil vapor retention.
Single acting. No vibrations.
Low noise level (62 dB).
Maximum working temperature: 40 °C.
Portable, they have a handle for transport.



Code 5900622



FILTER SILENCER FOR VACUUM PUMP
Code: 5515032

MODEL

Part No.	Pump rate m³/h	Vacuum limit mbar	Height / Width / Depth (exterior) cm	r.p.m.	Power W	Weight Kg
5900622	7,2	0.5	34 35 14	1400	180	11

SPARE PARTS

Pump connection kit: 1500019

Heated vacuum desiccator “Vacuo-Temp”

WITH TEMPERATURE THERMIC LIMITER.
TIME AND TEMPERATURE DIGITAL ELECTRONIC CONTROL.
ADJUSTABLE TEMPERATURE FROM AMBIENT +5 °C TO 170 °C.
STABILITY: ±2 °C. RESOLUTION: 1 °C.
TIME FROM 1’ TO 999’, OR CONTINUOUS.



FEATURES

AISI 304 stainless steel outer casing.
Polished aluminium alloy flat surface plate with an effective vacuum seal.
Tempered glass bell jar with silicon gasket seal.
Shielded heating element.
Pt 100 temperature probe.
Vacuum pump connection at the back of the unit.
Vacuum bleed valve.

CONTROL PANEL

Main switch.
Analogue vacuum gauge.
Digital time & temperature display.
Overheating alarm.
Visualized parameter indicator.
Push button for the visualized parameter.
Push button to increase the parameter.
Push button to decrease the parameter.
Button On-Off.

MODEL

Part No.	Vacuum Max	Usable volume litres	Ø heating plate cm	Heigth / Width /Depth (exterior) cm	Power W	Weight Kg
4000474	10^{-2} mm Hg	3	23.5	17 28 34	540	9

Supplied complete with bell jar and silicon seal.

SPARES

Tempered glass bell 15 cm high and 23 cm Ø.
Part No. 4000475
Silicon seal. Part No. 4000476

Desiccator for materials

WITH HYDROMETER CONTROL.



APPLICATIONS

Cabinet with protection against humidity and dust for anhydrous, biological and chemical preservation of samples.

FEATURE

Made of robust transparent 12mm thick methacrylate.
The door has a silicon seal and magnetic catch.
Volume: 55 Litres.
Dimensions 50 cm high x 38 cm wide x 29 cm deep.
Supplied complete with three perforated shelves and a stainless steel AISI 304 tray to hold desiccating material.
Part No. 1001403