COMECTA Precise analytical balance “JF-2204M”

COMECTA



NEW

USB

RS232

FEATURES

Digital 7 segment screen.
Time to stability: 8 seconds.
Adjustable time and sensitivity control.
ON/OFF automatic zero adjustment.
Automatic calibration with internal weight.
Tare range by subtraction up to the maximum capacity.
Piece counting function.
Hydrostatic weighing through lower acommodation.
Units of measurement in g, ct, and oz.
Adjustable Height. Level adjustment (bubble).
Data interface: RS-232/USB.
Operable ambient temperature 5 to 40 °C
Power supply: 110/220 V-50/60Hz.
Supplied complete with cover.

MODELS	Part No.	Maximum weight capacity g	Precision ±g	Linearity ±g	Height / Width / Depth (exterior) cm	Height / Width / Depth (Draft shield) cm	Ø plate cm	Weight Kg
JF-2204M	5830040	220	0.0001	0.0002	35 21.5 34	26.5 22 22,5	8	5

COMECTA Electronic Balance “Laborcom”

COMECTA

COMMON FEATURES

Display with easy-to-read seven-segment digits.
Stabilization time: 3 seconds.
ON/OFF. Automatic zero setting.
External automatic calibration.
Tare by subtraction up to maximum capacity.
Piece counting function.
Overload indicator.
Operating temperature: 5 to 35 °C.
Voltage: 220 V ±10 V / 50 Hz.

NEW DESING



MODELS	Part No.	Maximum weight capacity g	Precision ±g	Height / Width / Depth (exterior) cm	Ø plate cm	Weight Kg
LABORCOM 110-L	5830025	110	0,01	7 17,5 24	12,5	1,6
LABORCOM 210-L	5830026	210	0,02	7 17,5 24	12,5	1,6
LABORCOM 600-L	5830031	600	0,1	7 17,5 24	12,5	1,6
LABORCOM 1100-L	5830032	1100	0,1	7 17,5 24	12,5	1,6
LABORCOM 2100-L	5830033	2000	0,1	7 17,5 24	12,5	1,6
LABORCOM 11000-L	5830027	11000	1	7 17,5 24	16,5 x 16,5	1,8

COMECTA Mixing Balance “Hemo MIX 3”

TO MONITOR THE BLOOD DONATION IN BAGS

DELCON

FEATURES

The device handles up to 20 fully customizable donation workflows per PC and the target volume can be easily modified during donation.
3.2” high contrast screen; icon user interface; membrane keyboard
Movement: 3D with central axis, with programmable movement, with programmable pauses and clock-wise rotation reversal.
Export memory: MMC/ SD cartridges and USB memory
Power supply: 115/230 VAC. **Online frequency:** 50÷60 Hz
Internal memory: Up to 999 records
Battery capacity: Up to 70 donations with a fully charged battery



NEW

MEDICAL DEVICE CLASS I

USB

SD

MODEL

Part No.	Max weight Capacity g	Precision g	Resolution g	Height / Width / Depth (external) cm	Power VA	Weight Kg
5010010	999	± 2	1	23,5 35,1 27,3	45 máx	3,4

ACCESSORIES

Code bar scanner LSR /CCD. Code: 5010012
Batery Ni-Mh BAT-PK.12V *(Incluido de serie con la balanza)
Code: 5010011